

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List) ANDREAE FP (FR70, FR80, FR100)		CAS NUMBER: N/A DERIVATION: N/A		SYNONYMS: N/A USE: Paint booth floor covering		GENERAL	
Manufacturer's Name ANDREAE TEAM INC		Emergency Telephone Number 580-223-9334					
Address (Number, Street, City, State, and ZIP Code) PO BOX 2538 3550 Cypert Way ARDMORE OK 73402 USA		Telephone Number for Information 580-223-9334 Date Prepared: 03/04/08 Signature of Preparer (optional)					
Section II - Hazard Ingredients/Identity Information							
Hazardous Components (Specific Chemical Identity; Common Name(s))		OSHA PEL	OSHA STEL	ACGIH TLV	OSHA STEL	UNITS	WGT. %
Paper		N/A	N/E	N/A	N/E	N/A	<88 PPH
Proprietary Coating		N/A	N/E	N/A	N/E	N/A	>12 PPH
Carcinogenicity: Not listed as a carcinogen by the NTP, IARC, or OSHA.							
Section III - Physical/Chemical Characteristics							
Appearance: White paper.		Coefficient water/oil solubility: NA		Evaporation Rate (n-Butly Acetate=1): N/A			
Physical State: Solid, coated paper.		Partition coefficient (n-octanol/water): N/A					
Odor: none		pH: N/A		Vapor pressure (20C) (MM HG): N/A			
Odor threshold: N/A		Melting point: N/A		Vapor Density (air=1): N/A			
Specific Gravity (water=1): N/A		Boiling point: N/A		VOC: N/A			
Solubility in water (20C): Not soluble		Oxidizing properties: None known.					
Section IV - Fire and Explosion Hazard Data							
Flash Point (Method Used): N/A		Flammability Class: None		LEL: N/A		UEL: N/A	
Fire Retardant (Method Used): T461 om94 (TAPPI)		Autoignition temperature: Paper will char but not propagate flame.					
Extinguishing Media: Water, Multipurpose Dry Chemical							
Fire Fighting Procedures: Fire fighters should wear self-contained breathing apparatus and full protective clothing when fighting chemical fires.							
Unusual Fire and Explosion Hazards: Not determined							
Section V - Reactivity Data							
Chemical stability: Stable		Conditions to avoid: Keep away from heat, sparks, and flame. Avoid any source of ignition. Build up of paint like materials may effect flammability properties.					
Hazardous polymerization: Will not occur.							
Incompatibility (Materials to Avoid): NONE							
Hazardous Decomposition or Byproducts: NONE							
Section VI - Health Hazard Data							
Route(s) of Entry: None		Inhalation? None		Ingestion? May act as obstruction if swallowed.			
Skin? May cause slight irritation with excessive handling.							
Health Hazards (Acute and Chronic): NONE KNOWN							
Carcinogenicity: Not listed as a carcinogen.		NTP? None		IARC Monographs? None		OSHA Regulated? No	
Signs and Symptoms of Exposure: NONE KNOWN							
Medical Conditions Generally Aggravated by Exposure: NONE KNOWN							
Emergency and First Aid Procedures: N/A							
Section VII - Precautions for Safe Handling and Use							
Steps to Be Taken in Case Material is Released or Spilled: Restack or repackage.							
Waste Disposal Method: Clean floor paper can be discarded as non-hazardous material. Paint impregnated floor paper must be handled in accordance with EPA regulations 40 CFR parts 260-262, NAPA Standard #33, OSHA Regulation 1910, 107, and all local, state, and federal codes.							
Precautions to Be taken in Handling and Storing: Normal handling precautions. Store in a cool, dry area away from all ignition sources.							
Other Precautions: None							
Section VIII - Control Measures							
Respiratory Protection (Specify Type)							
Ventilation: local exhaust sufficient		Special: NONE					
Mechanical (General): None		Other: NONE					
Protective Gloves: Recommended		Eye Protection: Recommended					
Other Protective Clothing or Equipment: NONE							